



# UP-AND-OVER GARAGE DOORS

For single garages and parking spaces in collective garages

**HÖRMANN**



**STEEL DOORS.** The galvanized door leaves with polyester primer coating are optimally protected against adverse weather effects and corrosion right up to the cut edges. Our steel styles are available in inexpensive Traffic white as standard, in 7 equally-priced preferred colours as well as in about 200 colours based on RAL.





**EXCLUSIVE DOOR DESIGN.** With style 905, you can create a garage front to fit your own ideas and personal architectural style. A steel frame construction for on-site infill is a solid technical basis to build on. You can pick an infill to fit your individual style. This way you can incorporate your garage door harmoniously into the overall look of your home's facade.

Styles 902 and 905 also come with a practical wicket door that provides you with good access to everything in the garage, without the need to open the entire door.

**COLLECTIVE GARAGE DOORS.** Up-and-over doors are also suitable for the secure locking of parking spaces in collective garages. Varied ventilation slot sizes ensure optimum ventilation.

TOP LEFT. Style 905 with on-site infill

BOTTOM LEFT. Steel door style 902 Window grey RAL 7040 with wicket door


BOTTOM RIGHT. Steel door style 914, Traffic white, RAL 9016





# Equipment

For a secure and long-lasting door function



### Track guide with unique track well

The precise track guide **1** prevents the door leaf from derailing and also ensures smooth, quiet door travel thanks to wear-resistant plastic rollers. When the door is opened completely, it is cushioned by the stop and comes to a safe, reliable halt in the track well **2**.

### Comfortable closing and protection against trapping

Due to the specially shaped lever arm **3** the door pulls itself shut when closing. Flexible plastic rails between the door leaf and frame (no steel on steel), as well as additional protective caps over the lever arms, ensure effective protection against trapping.

### Multiple spring safety system **4**

If one of the springs breaks, the other intact springs support the door. The distance between the spring windings is so minimal that even children's fingers are protected from getting caught.

### Break-in-resistant locking

Thanks to the unique rotary catch lock **5**, the door leaf corners are fixed firmly to the frame, making forced opening practically impossible. You can additionally equip the door with top locking using an easy-to-fit retrofit kit.

### Stable door construction

The wide, galvanized block frame **6** and horizontal door leaf reinforcements **7** give the Hörmann up-and-over garage door high stability.

### Well protected

The standard bottom threshold rail **8** offers protection from rain and storms. In garages without a threshold, an optional flexible, weather-resistant rubber bottom profile **9** helps keep out passing debris.

## Steel doors





Style	902 <sup>1)</sup>	905	914
Traffic white RAL 9016, 7 preferred colours, RAL to choose	•		•
Wicket door and side door available	•	•	
Ideal for underground and collective garages			•
Max. width (mm)	3250 (5000 <sup>1)</sup> )	3000 (5000 <sup>1)</sup> )	3000
Max. height (mm)	2750	2500	2750

<sup>1)</sup> As up-and-over garage door N500 style 405 / 402; for more detailed information, please see the "Double and collective garage doors" brochure

# Dimensions and fitting data

Door type N 80 for single garages

## Arrangement of anchors



## Size range

Door height (BRH)	2750						
	2625						
	2500						
	2375						
	2250						
	2125						
	2000						
	1875						
		2000	2250	2500	2625	3000	3250
		Door width (BRB)					


## Standard sizes <sup>1)</sup>

Ordering sizes		Overall frame dimension	Clear passage dimension <sup>2)</sup>	Fitting behind the opening	Fitting in the opening
BRB	BRH	RAMB × RAMH	LDB × LDH	EFM width (EBB) × EFM height (EBH)	FM width × FM height
2250	1920	2355 × 1990	2110 × 1800	2250 (2215–2340) × 1920 (1890–1950)	2375 × 1970
	2000	2355 × 2070	2110 × 1880	2250 (2215–2340) × 2000 (1970–2030)	2375 × 2050
	2075	2355 × 2145	2110 × 1955	2250 (2215–2340) × 2075 (2045–2105)	2375 × 2125
	2125	2355 × 2195	2110 × 2005	2250 (2215–2340) × 2125 (2095–2155)	2375 × 2175
2375	1920	2480 × 1990	2235 × 1800	2375 (2340–2465) × 1920 (1890–1950)	2500 × 1970
	2000	2480 × 2070	2235 × 1880	2375 (2340–2465) × 2000 (1970–2030)	2500 × 2050
	2075	2480 × 2145	2235 × 1955	2375 (2340–2465) × 2075 (2045–2105)	2500 × 2125
	2125	2480 × 2195	2235 × 2005	2375 (2340–2465) × 2125 (2095–2155)	2500 × 2175
	2250	2480 × 2320	2235 × 2130	2375 (2340–2465) × 2250 (2220–2280)	2500 × 2300
2500	2375	2480 × 2445	2235 × 2255	2375 (2340–2465) × 2375 (2345–2405)	2500 × 2425
	1920	2605 × 1990	2360 × 1800	2500 (2465–2590) × 1920 (1890–1950)	2625 × 1970
	2000	2605 × 2070	2360 × 1880	2500 (2465–2590) × 2000 (1970–2030)	2625 × 2050
	2075	2605 × 2145	2360 × 1955	2500 (2465–2590) × 2075 (2045–2105)	2625 × 2125
	2125	2605 × 2195	2360 × 2005	2500 (2465–2590) × 2125 (2095–2155)	2625 × 2175
	2250	2605 × 2320	2360 × 2130	2500 (2465–2590) × 2250 (2220–2280)	2625 × 2300
	2375	2605 × 2445	2360 × 2255	2500 (2465–2590) × 2375 (2345–2405)	2625 × 2425
	2500	2605 × 2570	2360 × 2380	2500 (2465–2590) × 2500 (2470–2530)	2625 × 2550
	2750	2605 × 2820	2360 × 2630	2500 (2465–2590) × 2750 (2720–2780)	2625 × 2800
	2625	2125	2730 × 2195	2485 × 2005	2625 (2590–2715) × 2125 (2095–2155)
2750	2000	2855 × 2070	2610 × 1880	2750 (2715–2840) × 2000 (1970–2030)	2875 × 2050
	2125	2855 × 2195	2610 × 2005	2750 (2715–2840) × 2125 (2095–2155)	2875 × 2175
3000	2000	3105 × 2070	2860 × 1880	3000 (2965–3090) × 2000 (1970–2030)	3125 × 2050
	2125	3105 × 2195	2860 × 2005	3000 (2965–3090) × 2125 (2095–2155)	3125 × 2175

You can find up-and-over garage doors N500 up to 5000 mm width and additional door styles in the double and collective garage doors brochure.


## Fitting behind the opening

Horizontal view




Vertical view

Door without threshold




Vertical view

Door with threshold




## Fitting in the opening

Horizontal view




Vertical view

Door without threshold



Vertical view

Door with threshold



## Explanations

- BMB** Ordering size width
- BMH** Ordering size height
- BRB** Nominal size width
- BRH** Nominal size height
- RAMB** Overall frame dimension width
- RAMH** Overall frame dimension height
- LDB** Clear passage width
- LDH** Clear passage height
- GIM** Inside garage dimension
- EFM** Recommended structural dimension
- LF** Structural opening
- FM** Structural dimension
- EBB** Fitting area width
- EBH** Fitting area height
- OFF** Finished floor level
- AUSS** Exterior
- W** Overall length with operator  
ProMatic / SupraMatic:  
3200 mm up to 2500 mm door height  
3450 mm up to 2750 mm door height
- S** Required headroom:  
With steel infill ≥ 50 mm  
Style 905, 941 ≥ 65 mm  
with timber infill ≥ 65 mm

### Doors with modernisation panels

The structural width may be reduced by max. 10 mm. The structural height may be reduced by max. 10 mm if fitting with a threshold. Add 30 mm to the structural dimension for doors with continuous floor (frame from OFF).


- <sup>1)</sup> Depending on the door style
- <sup>2)</sup> LDH for door with threshold

Dimensions in mm

# Dimensions and fitting data

Door type F80 for pre-fabricated garages

## Arrangement of anchors



## Standard sizes <sup>1)</sup>


Ordering sizes	Overall frame dimension	Clear passage dimension <sup>2)</sup>	Structural opening <sup>1)</sup> fitting area
BRB × BRH	RAMB × RAMH	LDB × LDH	Width × Height
2325 × 1905	2459 × 2008	2185 × 1785	2399 - 2439 × 1948 - 1968
2350 × 1935	2484 × 2038	2210 × 1815	2424 - 2464 × 1978 - 1998
2375 × 2045	2509 × 2148	2235 × 1925	2449 - 2489 × 2088 - 2108
2375 × 2075	2509 × 2178	2235 × 1955	2449 - 2489 × 2118 - 2138
2425 × 2075	2559 × 2178	2285 × 1955	2499 - 2539 × 2118 - 2138
2455 × 1905	2589 × 2008	2315 × 1785	2529 - 2569 × 1948 - 1968
2480 × 1935	2614 × 2038	2340 × 1815	2554 - 2594 × 1978 - 1998
2485 × 2045	2619 × 2148	2345 × 1925	2559 - 2599 × 2088 - 2108
2500 × 2075	2634 × 2178	2360 × 1955	2574 - 2614 × 2118 - 2138
2500 × 2100	2634 × 2203	2360 × 1980	2574 - 2614 × 2143 - 2163
2560 × 2125	2694 × 2228	2420 × 2005	2634 - 2674 × 2168 - 2188
2570 × 2125	2704 × 2228	2430 × 2005	2644 - 2684 × 2168 - 2138
2590 × 2075	2724 × 2178	2450 × 1955	2664 - 2704 × 2118 - 2138
2590 × 2125	2724 × 2228	2450 × 2005	2664 - 2704 × 2168 - 2188
2705 × 2125	2839 × 2228	2565 × 2005	2779 - 2819 × 2168 - 2188
2715 × 2075	2849 × 2178	2575 × 1955	2789 - 2829 × 2118 - 2138
2720 × 2200	2854 × 2303	2580 × 2080	2794 - 2834 × 2243 - 2263
2730 × 2125	2864 × 2228	2590 × 2005	2804 - 2844 × 2168 - 2188



## Plug-and-screw fitting


### Horizontal view

(min. 75 mm reveal depth)




### Vertical view

Door without threshold



### Vertical view


Door with threshold



## Clamp fitting


### Horizontal view

(min. 50 mm, max. 100 mm reveal depth)



### Vertical view

Door without threshold



## Explanations

- BMB** Ordering size width
- BMH** Ordering size height
- BRB** Nominal size width
- BRH** Nominal size height
- RAMB** Overall frame dimension width
- RAMH** Overall frame dimension height
- LDB** Clear passage width
- LDH** Clear passage height
- W** Overall length with operator ProMatic / SupraMatic 3200 mm (up to 2500 mm door height)
- OFF** Finished floor level
- AUSS** Exterior
- OW** Opening angle 180°

<sup>1)</sup> Depending on the door style

<sup>2)</sup> LDH for doors without threshold + 30 mm


Dimensions in mm

# Dimensions and fitting data


## Side doors

### Single-leaf with corner frame

Vertical view door without threshold




Horizontal view




### Double-leaf with corner frame

Vertical view door with threshold




Horizontal view




### Single-leaf with 65 mm block frame

Vertical view door without threshold



Horizontal view



### Standard sizes, single-leaf

Ordering size		Structural opening						Clear passage dimension		Lever height
		With corner frame		With 65 mm block frame		With 32 mm block frame / clamp-on frame		With threshold <sup>2)</sup>		
BRB	BRH	LMB	LMH	LMB	LMH	LMB	LMH	LDB	LDH	From OFF approx.
875	1875	885	1880	1010	1942	945	1910	830	1837	990
	2000	885	2005	1010	2067	945	2035	830	1962	1050
	2125	885	2130	1010	2192	945	2160	830	2087	1115
1000	2000	1010	2005	1135	2067	1070	2035	955	1962	1050
	2125	1010	2130	1135	2192	1070	2160	955	2087	1115

Special sizes and versions on request, max. size range (BR): 1250 × 2375 mm.

Standard sizes with steel infill and on-site infill are supplied for external fitting as standard. Internal fitting is possible by reversing the hinges. Styles with timber infill overlapping the frame are only possible with external fitting.


### Size range for double-leaf side doors with corner frame or 65 mm block frame

Width (BRB) 1300 to 2500 mm  
Height (BRH) 1750 to 2250 mm


As standard delivered for external fitting, traffic leaf on right-hand side, state on order if internal fitting or traffic leaf on left-hand side is required!

## Double-leaf with 65 mm block frame

Vertical view door with threshold




Horizontal view



## Fitting variants side doors

External fitting opening outwards


Single-leaf



Left-hand hinged

Right-hand hinged

Double-leaf




Traffic leaf  
Left-hand hinged


Traffic leaf  
Right-hand hinged

## Single-leaf with 32 mm block frame

Vertical view door with threshold




Horizontal view




## Single-leaf with clamp-on frame

Vertical view door with threshold



Horizontal view



## Explanations

<b>BMB</b>	Ordering size width
<b>BMH</b>	Ordering size height
<b>BRB</b>	Nominal size width
<b>BRH</b>	Nominal size height
<b>LMB</b>	Structural opening width
<b>LMH</b>	Structural opening height
<b>RAMB</b>	Overall frame dimension width
<b>RAMH</b>	Overall frame dimension height
<b>LDB</b>	Clear passage width
<b>LDH</b>	Clear passage height

The clear passage width is reduced if the opening angle is less than 180°.

<b>OFF</b>	Finished floor level
<b>AUSS</b>	Exterior
<b>OW</b>	Opening angle 180°
<b>SF</b>	Fixed leaf
<b>GF</b>	Traffic leaf

<sup>1)</sup> Recess on-site in the area of the U-shaped latch in rebate

<sup>2)</sup> LDH for side door without threshold, single-leaf + 15 mm, double-leaf + 20 mm

## Please note:

With doors fitted on the inside, the threshold angle or transport angle must always be removed and a water run-off to the outside must be provided. Doors on the weather side are preferably fitted externally.

Dimensions in mm

# Experience Hörmann quality in new construction and modernisation

Hörmann provides an excellent basis for comprehensive planning. Carefully matched solutions offer you the very best in perfectly designed products for every area.

**GARAGE DOORS. GATE AND DOOR OPERATORS. ENTRANCE DOORS.  
RESIDENTIAL INTERNAL DOORS. STEEL DOORS. FRAMES.**



Some of the doors shown are equipped with special equipment and do not always correspond to the standard versions. The surface finishes and colours shown are subject to the limitations of the printing process and cannot be regarded as binding. All rights reserved. No part may be reproduced without our prior permission. Subject to changes.